

CE/DG-2

General Description-

4 tips Natural grain leather driver gloves



Glove Material

Palm – Natural grain leather Back –
Natural grain leather

Cuff –Natural grain leather cuff with elasticized back

Binding –Synthetic red binding

EN 388:2016 & 420+ A1:2009

PERFORMANCES DATA

Abrasion resistance

Performance level 2

Blade cut resistance

Performance level 1

Tear Resistance

Performance level 2

Puncture resistance

Performance level 3

Dexterity

Performance level 5

Available sizes: 7 to 11(According to EN420 sizing standards)

Application

- Construction
- Industrial Manufacturing
- Material Handling
- Small Parts Assembly

Advantages

- Excellent for general use
- Excellent physical properties,
- good dexterity
- Excellent abrasion resistant.
- Chromium VI level maintained as per EN 420 standards

European Conformity

The gloves complies with the European Directive Regulation (EU) 2016/425, notably regarding ergonomics, innocuousness, comfort, ventilation and flexibility, with EN 388:2016 EC –Type Examination Certificate for the final product by **SGS United Kingdom , Notified Body 0120**

Construction	Liner	GSM of palm	GSM of back	Total weight/pair (g)
4 tips natural grain leather driver glove	NA			84 (Size 7) 94 (Size 8) 108 (Size 9) 115 (Size 10) 130 (Size 11)
Thikness of Palm (mm)	Thickness of back (mm)	Cuff	Binding	Packing
0.8 - 1.0	0.8 - 1.0	Grain leather elasticized cuff	Synthetic	12 pairs in a primary packet 10 packets in a carton